

Triple-Phase Network Analyzer / RS485 Modbus



CE

- ▶ INPUT: up to 600 Vac, 5 Arms (S203TA), 100mA (S203T)
- ▶ OUTPUT: N.1 channel current 0..20, 4..20 mA or voltage 0..5, 0..10 Vdc
- ▶ INTERFACE:
 - RS485 serial communication with Modbus–RTU protocol
 - Analogue output configurable to Vrms, Irms, Watt (bi-directional), $\cos\Phi$
- ▶ Insertion: single phase, Aron (three-phase with N.2 CT), four wires (three-phase with N.3 CT)
- ▶ Accuracy: 0,5% (S203TA), 0,2% (S203T)
- ▶ Galvanic isolation @ 3,75 KV
- ▶ Din rail mounting
- ▶ Power supply: 10..40 Vdc, 19..28 Vac



PLCs



Acquisition



Instruments



Data logger



Power



HMIs



Switches



Motion



Sensors



Converters



Keyboards



SCADA



Telemetry

TECHNICAL SPECIFICATIONS

S203T / S203TA - Triple-Phase Network Analyzer / RS485 Modbus



SERIAL LINE ACCESSORIES

K107A – RS485 ↔ RS485 isolator repeater

K107B – RS232 ↔ RS485 converter

K107USB (S107USB) – USB ↔ RS485 converters din rail mounting or portable version (S107USB)

GENERAL FEATURES

Power supply	10÷40Vdc, 19÷28 Vac
Channels	single phase, Aron (three-phase with N.2 CT), four wires (three-phase with N.3 CT)
Accuracy	- 0,5% (S203TA) - 0,2% (S203T)
Status indicators	- Power - Fail - Communication on Rs485
Galvanic Isolation	- Input//Power supply and Input/Output at 3750 Vac - others at 1.500 Vac
Hot swapping	Yes
Power consumption	max 2,5 W
Protections for inputs	Against Surges: up to 4kV
Humidity	30..90% a +40°C (not condensing)
Response time	400 ms

INPUT

Type Voltage: max 600 Vac, 50-60 Hz
Current: 5 Arms (S203TA), 100mA from CT (S203T)
- Single phase
- Aron (three phase with N.2 CT)
- Four wires (three-phase with N.3 CT)

ORDER CODE

Cod.

S203T (input 100mA, from CT)

S203TA (input 5A)

Accessories & Software

TA15: Current transformer (CT) - 15A / 100 mA

TA25: Current transformer (CT) - 25A / 100 mA

TA100: Current transformer (CT) - 100A / 100mA

Z-NET3 - configuration software downloading from www.seneca.it


Design	Terminal housing for mounting on 35 mm DIN 46277
Data memory	EEPROM for all configuration data; storage time: 10 years.
DIP Switch	- Address setting - Baud rate setting - Selection of inserction type - Selection of 3 phase o 1 phase - Output
Enclosure	"V0" self-extinguishing glass filled nylon case
Dimensions	105 x 89 x 60 mm (w x h x d)
Weight	About 300 g
Operating temperature	-10..+65 °C
Connections	Removables 3- way screw terminals, 5,08 mm
IP Protection	IP 20
Standards	EN61000-6 EN61010-1 EN60742
Approvals	CE

INTERFACE / OUTPUT


Type Rs485 Modbus RTU slave: 1200...115200 baud rate
Analogue output: corresponding at Vrms, Irms, Watt, cosΦ

CONNECTIONS




Power Supply



RS485



Inputs



Outputs

