

LBISPPM8415051-XN25C0-CB0J02

IP65 Stainless Bezel Panel Mount 15" 1024x768, 250nits, Intel® Atom™ D525 Processor



Features

- 15" LCD panel, 1024 x 768, 250 nits
- Intel® Atom™ D525 Processor
- Intel @ D525 + ICH8M
- 1 x 200-pin DDR3 SODIMM up to 4GB
- 1xVGA, 6xUSB, 3xCOM, 2xLAN
- 1xPS2, Mic-in, Line-in, Line-out



| | | |
|-----------------|---------------------------|--|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspec Ratio / Size | 4 : 3 / 15" viewable diagonal area |
| | Active Area / Pixel Pitch | 304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm |
| | Native Resolution / Color | 1024(H) x 768(V) / 16.2 Million |
| | Brighthess / Contrast | 250 cd/m ² (typ) / 700 : 1 |
| | Response Time | ≤ 35 ms |
| | Viewing Angle (Typical) | H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°) |
| | Light Source | LCD TFT |
| System | CPU | Intel® Atom™ D525 Processor ; FSB 667MHz |
| | BIOS | Award 16MB SPI |
| | System / Graphic Chipset | Intel @ D525 + ICH8M / Intel® D525 Integrated |
| | System Memory | 1 x 200-pin DDR3 SODIMM up to 4GB |
| | HDD | 2 x SATA |
| | I/O Ports | 1 x VGA |
| | | 6 x USB |
| | | 3 x COM (RS232) |
| 2 x RJ45 | | |
| 1 x (KB and MS) | | |
| | Mic-in, Line-in, Line-out | |
| Expension | 1 x Mini PCI-e | |
| Power | Power Input | ATX or DC 12V Input |
| | Power Consumption | 33 Watt, <1 Watt |
| Environmental | Operating Temperature | -5°C ~60°C (23°F ~140°F) |
| | Operating Humidity | 0%~95%(non-condensing) |

| | | | | |
|---------|-----------------------|-----------------------|-----------|----------------------------|
| Options | Touch | Enhanced Pane | Other | |
| | Resistive(With Glass) | High Brightness Panel | WiFi | Networking Digital Signage |
| | Capactive | Panel-LED Backlight | 3G | Web Cam |
| | SAW | Wide Temperature | Bluetooth | Motion Sensor |
| | | Wide Viewing Angle | RFID | Auto LightSensor |
| | | Sunlight Readable | | Auto-Dimming |

