

LBISPPM8417051-EN30C0-CB0J02

IP65 Stainless Bezel Panel Mount 17" 1280x1024, 300nits, Intel® Atom™ D525 Processor



Features

- 17" LCD panel, 1280 x 1024, 300 nits
- Intel® Atom™ D525 Processor
- Intel® D525 + ICH8M
- 1 x 200-pin DDR3 SODIMM up to 4GB
- 1xVGA, 6xUSB, 3xCOM, 2xLAN
- 1xPS2, Mic-in, Line-in, Line-out



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	4 : 3 / 17" viewable diagonal area
	Active Area / Pixel Pitch	337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V) mm
	Native Resolution / Color	1280(H) x 1024(V) / 16.7 Million
	Brighthness / Contrast	300 cd/m ² (typ) / 800 : 1
	Response Time	≤ 5 ms
	Viewing Angle (Typical)	H. 170° (- 85° ~ + 85°) , V. 160° (- 80° ~ + 80°)
	Light Source	CCFL, Long life, 50,000 hrs (typ)
System	CPU	Intel® Atom™ D525 Processor ; FSB 667MHz
	BIOS	Award 16MB SPI
	System / Graphic Chipset	Intel® D525 + ICH8M / Intel® D525 Integrated
	System Memory	1 x 200-pin DDR3 SODIMM up to 4GB
	HDD	2 x SATA
	I/O Ports	1 x VGA
		6 x USB
		3 x COM (RS232)
2 x RJ45		
1 x (KB and MS)		
	Mic-in, Line-in, Line-out	
Expension	1 x Mini PCI-e	
Power	Power Input	ATX or DC 12V Input
	Power Consumption	43 Watt, <1 Watt
Environmental	Operating Temperature	-5°C ~ 60°C (23°F ~ 140°F)
	Operating Humidity	0%~95%(non-condensing)

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming

