

# LBISPPM8419051-EN25L0-CB0J08

IP65 Stainless Bezel Panel Mount 19" 1280x1024, 250 nits, Intel Core i7/i5/i3 Celeron Processor



## Features

- 19" LCD panel, 1280 x 1024, 250 nits
- Intel Core i7/i5/i3 Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out



Panel	Cell Type	TFT LCD
	Aspec Ratio / Size	4 : 3 / 19" viewable diagonal area
	Active Area / Pixel Pitch	376.32(H) x 301.06(V) mm / 0.294(H) x 0.294(V) mm
	Native Resolution / Color	1280(H) x 1024(V) / 16.7 Million
	Brighness / Contrast	250 cd/m <sup>2</sup> (typ) / 800 : 1
	Response Time	≤ 5 ms
	Viewing Angle (Typical)	H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)
	Light Source	LED, Long life, 35,000 hrs (typ)
System	CPU	Intel Core i7/i5/i3 Celeron Processor
	BIOS	UEFI
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
	HDD	4 x SATA2
	I/O Ports	1 x VGA
		2 x COM
		1 x HDMI
6 x USB(2.0)		
2 x LAN		
Expansion	Audio Line In	
1 x Mini PCI-E (Half Size)		
Power	Power Input	ATX PWR (24+4 pin)
	Power Consumption	72 Watt, <1 Watt
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)
	Operating Humidity	0%~95% (non-condensing)

Options	Touch	Enhanced Pane	Other		
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage	
	Capactive	Panel-LED Backlight	3G	Web Cam	
	SAW	Wide Temperature	Bluetooth	Motion Sensor	
		Wide Viewing Angle	RFID	Auto LightSensor	
		Sunlight Readable		Auto-Dimming	

