



USB to 1-Port RS-422, RS-485, RS-530 DB25 Serial Interface Adapter

Part: 2102 Model: SeaLINK+485

The 2102 USB serial interface adapter provides a single USB to RS-422, RS-485, or RS-530 serial port for providing USB connectivity to legacy or non-USB compliant devices. SeaLINK® serial interface adapters support standard PC data rates up to 921.6K bps to provide you with the horsepower your serial I/O applications require.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, simply connect the SeaLINK serial interface adapter to your USB port and the device is immediately recognized by the system as a standard serial port.



Features

- Compliant with RoHS and WEEE directives
- Configurable for RS-422, RS-485, or RS-530
- High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- Data rates to 921.6K bps
- Automatic RS-485 enable/disable
- All modem control signals implemented
- Hot-swappable
- Powered by USB connection
- DB-25M connector
- Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- Includes 6' USB device cable (Item# CA179)



Cobots



Artificial Vision



PLCs



HMIs



Sensors



Dataloggers



Software



Gateways



Oscilloscopes



Load cells



DAQ / IoT



Industrial PCs

USB to 1-Port RS-422, RS-485, RS-530 DB25 Serial Interface Adapter

Part: 2102 Model: SeaLINK+485

Specifications

Family

- SeaLINK

Communications Chip

- USB/UART

Dimensions

- 3.8" (L) x 2.3" (W) x 1.0" (H) 9.66 cm (L) x 5.84 cm (W) x 2.54 cm (H)

Electrical Interface

- RS-422, RS-485, RS-530

High Retention USB

- Yes

Humidity Range

- 10 – 90% Relative Humidity, Non-Condensing

Host Interface(s)

- USB

Max Data Distance

- 4000 feet

Max Data Rate

- 921.6K bps

Operating Temperature

- 0°C to 70°C (32°F to 158°F)

of Ports

- 1

Power Requirement

- +5V @ 50mA

RoHS Compliant

- Yes

Serial Connector(s)

- DB25M

Storage Temperature

- 0°C to 70°C (32°F to 158°F)

USB Powered

- Yes

USB Specification

- 1.1 Compliant, 2.0 Compatible



Cobots



Artificial Vision



PLCs



HMIs



Sensors



Dataloggers



Software



Gateways



Oscilloscopes



Load cells



DAQ / IoT



Industrial PCs