

All the patents are held accountable counterfeiting.

Features



Green Power

- Standard/Din Rail Mounting Dual Purpose
- No-load Consumption is lower than 0.3W
- Comply with High Efficiency Power 80Plus Criterion
- Comply with 2010. Energy Conservation Power Erp Regulation
- Convection cooled high reliability
- 100% burn-in test
- 1 years warranty
- Output modify range: 3V~200VDC

DIMENSIONS:102(H)\*35(D)\*45(W)mm

WEIGHTS: 117g

General specifications

INPUT

Input range 90~264VAC  
127~380VDC  
Input frequency 47~63Hz  
Inrush current (25°C) 40A/110VAC  
80A/220VAC

No Frame Ground Design

OUTPUT

Hold-up time 13ms  
Short protection Autorecovery  
Over load protection Automatic power limited

Detail specifications

20~25 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) <sup>1</sup>			Ripple & Noise <sup>4</sup>	Line REG. <sup>2</sup>	Load REG. <sup>3</sup>	Efficiency <sup>5</sup>	O.V.P
		Min.	Rated	Max.					
LP1020D-05S	V : +5V ±10%	0A	4A	4A	80mV	±1%	±1%	82% Ref.	7.13 ~ 7.88V
LP1025D-12S	V : +12V ±10%	0A	2.1A	2.1A	120mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V
LP1025D-24S	V : +24V ±10%	0A	1A	1A	240mV	±1%	±1%	86% Ref.	31.4 ~ 34.7V

CE Standards

EN 55032, EN 55024,  
EN 61000-3-2, EN 61000-3-3,  
(EN 61000-4-2, EN 61000-4-3,  
EN 61000-4-4, EN 61000-4-5,  
EN 61000-4-6, EN 61000-4-8,  
EN 61000-4-11)  
LVD: EN 60950-1

Safety Standards



UL 508 APPROVAL



CE Marking



Double Insulated

Environments

Operating Temperature -15 ~ 50°C, Ambient  
Operating Humidity 20 ~ 90% RH, No Condensing  
Storage Temperature -20 ~ 85°C, Ambient  
Vibration 2G, 10~500Hz, 3 axes

NOTE

1. Each output can provide up to maximum load, but total load can not exceed rated output power.
2. Line regulation is measured from low line to high line at rated load.
3. Load regulation is measured from 20% to 100% of rated load at 220VAC input.
4. Ripple & Noise are measured with 20MHz oscilloscope at 220VAC by using a 20cm long 12" twisted pair-wire with a 0.1uF/630V metal capacitor & a 47uF electrolytic capacitor parallel on the test point.
5. Efficiency is measured at rated load and 220VAC input.
6. Hold-up time is measured at rated load and 220VAC input.
7. Output Voltage Adjustable is measured on 5% of rated load.
8. Reign Power reserve the right to change specifications at any time without notice.