



## Introduction

MB200 is a brand new compact design which is especially for ticketing, stocktaking or logistic market. With its tiny body, it can be easily carried in pocket or bag for mobility application. It can easily connect to the mobile device as a host by Bluetooth technology and transfer all the scanned data immediately to the corresponding application program.

With its auto-shuttle-emulation-like smart detection that offers superior decoding on a reading speed up to 500 scans per second and up to 500mm reading depth for the majority of 1D barcodes, the scanner delivers excellent decoding performance.

MB200 is absolutely a high performance compact barcode scanner that provides the most cost-effective solutions in the market. It is perfectly suitable and definitely the best choice for the application with mobile devices.

### Features

- Easy Control With 2 Buttons
- Rechargeable Li-Poly Battery With User Compartment for Easy Replacement
- Data Transmission via Bluetooth V2.1+EDR(Class2, HID/SPP)
- High Performance with CCD/ 2D / Laser Scan Module
- Large Data Storage of 4MB Memory
- Reliable Design to Fulfill 1.5m Meter Drop Threshold, IP54-Rated

Logicbus

• Easy Development in AP

# **MB200**

## **Specifications**

#### • System

Power Source

Dimensions

Available color

Weight

Hanger Protection

Drop Spec.

**Battery Charging** 

• Physical Characteristics

Battery

Micro Processer	32-bit
Operating Platform	Proprietary
Flash Memory	128 Kbyte program. 8M bytes user data that can save over 100,000 itemsof 50 bytes barcode data.
RAM Memory	20 Kbytes
Input Keys	2 buttons, include 1. scan and confirm trigger button, 2. upward scroll button ,
Indicator	1. LED x 1 2. Beeper x 1 3. Vibrator x 1

Lithium-Polymer (3.7V DC, 550mAh)

41.8mm x 89.9mm x 23.6mm ( W x D x H )

Black cover and dark gray bottom cases

Designed to be approx. 70 g

1 Hanger Hole

1.5m (5 feet)

IP54 sealing protection

via Micro USB connector

#### • Data Input

3 Options: by respective rollout schedule.
One of the barcode scanners
(1) CCD 1D Scanner
(2) 2D imager scanner
(3) Laser 1D scanner

#### • Communication Interface

Wired	Micro USB V2.0 ( for Power charge and Batch data transmission)
Wireless	Bluetooth 2.1 + EDR

#### • Functions

Standby Duration	Over 3 months
Scan per charge	50,000 scans [BT off] / 5000 scans[BT On] under normal operating conditions after battery full charged.
Low Battery Alert	Battery levels are indicated by the LED illuminating color
Data Handling	Able to be chosen as on-line (via BT or Wifi) or off-line (batch) mode.
Off-line Mode	Can save over 50,000 items of 50 bytes barcode data.
Indication combination	Can be configured as (1) LED indication (2) LED indication + Beep (3) LED indication + Vibration
Compatibility	Customers can easily develop AP on different OS.

\*Specifications and features are subject to change without prior notices\*



1043 Broadway Ste 103 Chula Vista, CA. 91911 USA Ph:(619)-616-7350