## APPLICATION

"bun THERMO" is a water proof (IP68) temperature recorder and alarm system. It is powered by 2 replaceable AA batteries for up to 10 years and connects directly to Wi-Fi.

More than an accurate meter and a reliable logger, "bun THERMO" is also a cloud-based alarm system.

All setting parameters like measurement intervals, upload intervals, and minimum and maximum allowed temperature thresholds can be set through a web-based application on any platform. It sends out email and text message alarms as soon as any temperature exceeds or falls below pre-set limits. It also provides access to the records history, graphs and periodical reports. Its hardware and software installation is very easy and does not require any specific tools or applications.



## GENERAL SPECIFICATIONS

Built in sensors		Temperature		
Temperature measurement range	°C	-25 to +70		
	°F	-13 to +160		
Upload temperature range*	°C	°C -5 to +70		
	°F	20 to +160		
Temperature measurement accuracy	°C	± 0.3 (down to ± 0.2 by order) (± 0.55 °F)		
Power supply		2 x AA replaceable batteries		
Protection class		IP 68		
Compliances		IEEE 802.3, EN 61326-1, EN 61010, EN 12830,		
		FCCID: 2AHMR-ESP12F, CE, ROHS, HACCP		
Battery life*		Up to 10 years		
Upload intervals		One hour to once a week (or on demand)		
Record intervals		1 minute to 120 minutes (down 2 sec. by order)		
Interface		Wi-Fi - IEEE 802.3 – 2.4 GHz		
Max. number of internal records		16,384 – Automatic cloud sync and replace		
*Unload temperature range is the ambient condition required for the device to stay fully operational. These				

\*Upload temperature range is the ambient condition required for the device to stay fully operational. These operations include being able to connect and sync with the cloud and send out alarms. However, the device can continue recording the data in its internal memory while in temperature measurement range.

\*Depends on reading and upload intervals and environmental conditions. Battery life is more than 10 years in a standard set up. (Standard set up is room temperature 20°C measurement every 15 minutes upload every 48 hours).

www.logicbus.com.mx

Guadalajara (33) 3823-4349

(55) 8995-3820

D.F.

AMBIENT CONDITIONS			
Storage temperature	°C	-25 to +75	

DIMENSIONS		
Diameter (max.)	L	mm 80.0
Height (max.)	Н	mm 34.5

## **KEY FEATURES**



Direct Wi-Fi connection



Access to your records on all devices



Waterproof & washable



Graphs, reports & detailed records



Up to 10 years of battery life

Email & text

message alarms



Push alarm for out of range registration



Cloud storage For +20 years

Guadalajara (33) 3823-4349 D.F. (55) 8995-3820

USA (619) 616-7350