

Multiway Robotics

Slim Yet Powerful

WeFront X20

- © Light-weight and low requirements for ground bearing capacity; supporting cross-floor handling; stable operation
- Applicable to extremely narrow passages, increasing space utilization in factories
- Modular design, allowing for super fast and flexible deployment





























Limited Space, Unlimited Wisdom



Laser SLAM Navigation

No need to renovate the on-site environment



Applicable to Multiple Scenarios

Suitable for ground handling, high-floor handling, cross-floor handling by elevator, etc.



Five Layers of Safety Protection

Sound & light warning

Front obstacle avoidance/rear 3D visual obstacle avoidance

3D visual stereo obstacle avoidance

Emergency stop button

Control system protection: path deviation, positioning fault, component fault, communication fault































Technical Specifications

Navigation	Laser SLAM	•
Communication	Wireless Wi-Fi	•
	Optical Communication	0
	5G	0
Basic Specifications	Rated Load (kg)	2000
	Dimensions L×W×H (mm)	1613x735x(1940/2140/2340)
	Fork Dimensions I/e/s (mm)	1150×173×60
	Turning Radius (mm)	1360
	Climbing Capability (mm)	≤3° (5%)
	Weight (kg)	480
Movement Features	Driving Features	Forward, backward, turn
	Driving Speed (m/s)	1.3/1.1
	Positioning Precision (mm)	±5
	Stop Angle Accuracy (°)	±1
	Manual/Auto	•
Safety Protection	Path Deviation Protection, Positioning Fault Protection	•
	Component Fault Protection, Communication Fault Protection	•
	Bottom Obstacle Avoidance Radar	•
	Fork Head Anti-Collision Detection	•
	Stereo Obstacle Avoidance	0
	Emergency Stop Button	•
	Sound & Light Warning	•
	НМІ	•
Battery Specifications	Charging Mode	Auto/Manual
	Power Swap Mode	•
	Power Swap Mode	Disassemble
	Battery Type	Lithium iron phosphate
	Rated Voltage (V)	48V
	Standard Capacity (Ah)	30 Ah
	Number of Charge Cycles	2000 charging cycles
	Charging Pile Specifications	48V 50A
Visual Function	Goods Presence Detection	•
	Goods In-Place Detection	•
	Pallet Pose Identification	0
	On-Fork Goods Appearance Detection	0
	Barcode/RFID Identification	0

■ Standard ○ Optional
























Cross-Floor Handling by Elevator



The cross-floor handling function makes it suitable for multi-floor and multi-area material handling applications. With the equipment control system MW-WCS, it can automatically interact with elevators or automatic doors and therefore enter/exit them to walk between different floors and areas.

Visualized Information, Easily Track Vehicles at Any Time









Low Investment, High Return - Truly Cost-Effective





Reduced Operational Costs

It can save labor costs and other administrative costs, reduce maintenance costs, prevent accidents, and ensure safe production.

Increased Productivity

The optimized automation process and on-site system management can improve productivity, enable a 24-hour stable operation, and improve the company's management capacity.

Accelerated Intelligent Manufacturing Upgrade

The use of big data enables the interconnection with other logistics equipment and warehousing equipment, which extends single product application to systematic application and allows for overall optimization.

